

Built for Your



Industry



(a subsidiary of Bright Coop, Inc.)

built the way you want it for the way you use it!

42' Oilfield Float

Weight 16,240 lbs. Plus or Minus 3%

Model: VFO42102



For use in the oil and gas industry, The Viking 42' Oilfield Float provides quick and easy loading with retractable landing gear and pick-up eye for winch use. The heavy duty 8-5/8" tail roller assembly handles the heavy loads and designed with service in mind. The bearings are replaceable and greaseable. The 42' Oilfield Float makes it easy to get around worksites and will hold up to the task. This trailer is built Viking tough! Capacity: 100,000 lb. GVWR.



Built for Your



Industry




(a subsidiary of Bright Coop, Inc.)

built the way you want it for the way you use it!

42' Oilfield Float

Model: VFO42102



102" Wide Weight 16,240 lbs. Plus or Minus 3% Capacity: 100,000 lb. GVWR

Features:

- Mainframe..... 24" Fabricated main beams, 3/4" x 6" top and bottom flange with 3/16" web welded on both sides, 3/8" web in the neck. All flange and web material is high strength steel.
- Crossmembers... 6" x 3.7# Jr. I beam on 12" centers.
- Kingpin..... 2" SAE kingpin, 3/8" kingpin plate, 24" kingpin setting (standard).
- Siderails..... 8" x 11.5# Structural channel with 1/4" formed stake pockets. 3/8" x 3" Rubrail with double pipe spools.
- Suspension..... Watson-Chalin® 50,000 lb. 7 leaf single point spring suspension.
- Axles..... (2) 25,000 Lb., 5" round, 5/8" wall.
- Brakes..... 16-1/2" x 7", Type 30/30 brake chambers, outboard drums, Meritor WABCO® (2S/1M) ABS on one axle.
- Wheels..... 8.25 x 24.5, Steel 10 hole disc, hub piloted (color: white).
- Tires..... 11R x 24.5 Radials.
- Landing gear..... Heavy duty folding schedule 80 pipe, winch retractable.
- Finish..... Shotblasted and painted with a high solid polyurethane paint. Colors: black or red (standard). Optional: epoxy or zinc-rich primer available.
- Floor..... Flush mounted 1-3/8" Apitong (standard) smooth steel plate located over the tandem areas.
- Lights..... 7-Way main receptacle, sealed wiring harness with rubber mounted LED lights. 3 Lights per side including mid-turn.
- Tandem..... 60" Fixed tandem setting.
- Pin pockets..... (8) Total (4) per side.
- Pipe pockets..... (4) Total (2) per side.
- Tail roller..... 8-5/8" Tail roller with (2) sets of overload rollers.
- Rear bumper..... Heavy duty pipe bumper with high visibility reflective conspicuity tape.
- D-rings..... (2) Located at the vertical supports on the rear bumper for towing.

Options:

- Inverted fifth wheel
- 1" D-rings
- Sliding winches
- Rear pull loop

Viking Specialized Trailers
1730 S.W. Stalling Dr.
Nacogdoches, Texas 75964
(936) 564-8370 (800) 562-0730
Fax (936) 205-9171
www.vikingspzdtrailers.com